



Valves | Water Control Valves (OS&Y and NRS Gate Valves) | [Gate Valves, Outside Screw and Yoke](#)

Model OSY-6000

Product Description

Resilient Seated Gate Valves. 14 through 24 in. NPS. Available with the following end connections and rated working pressures:

Product Specification

Model No	Valve Size		Rated Working Pressure		End Connection
	in	(mm)	psi	(kPa)	
OSY-6000	14, 16, 18, 20, 24	(350, 400, 450, 500, 600)	250	(1720)	Flange × Flange (ANSI, BS10, EN1092)
OSY-6000	14, 16, 18, 20, 24	(350, 400, 450, 500, 600)	200	(1375)	Flange × Flange (ANSI, BS10, EN1092)

Details

Category	Gate Valves, Outside Screw and Yoke
Class of Work	1120 - OS&Y and NRS Gate Valves
Approval Standard	FM 1120, 1130 - Fire Service Water Control Valves (OS&Y and NRS Type Gate Valves)
Certification Type	FM Approved
Listing Country	United States of America

Company

Sentry Sprinklers by GLC Fire Systems Inc.
 10967 Lake Underhill Road, Unit 102,
 Orlando , Florida 32825
 United States of America
<http://sentrysprinklers.com>