UL Product iQ®



SIN SY8112

File Number: EX28273

COMPANY

Sentry Sprinklers Owned by GLC Fire Systems Inc

10967 LAKE UNDERHILL RD, UNIT 102 ORLANDO, FL 32825 United States

SIN INFO

SY8112

Glass Bulb Type

Response	Sprinkler Type	Nom K-Factor, gpm/vpsi	System Working	Corrosion
Туре	. ,,	(L/min/vbar)	Pressure	Resistant
QR	Standard-Spray Sprinklers, Upright And	5.6 (80)	175 psig (1.2 Mpa)	Not Available
	Pendent			

GENERAL					
Inlet Connection					
1/2 in. NPT					

STANDARD-SPRAY SPRINKLERS, UPRIGHT AND PENDENT				
Туре	Sprinkler Temp Rating, °F (°C)	Cover Temp Rating, °F (°C)		
Upright	135 (57), 155 (68), 175 (79), 200 (93)	Not Applicable		



Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2024 UL LLC."

product.